

View Online at <https://aerobasegroup.com/nsn/5920-00-519-4274>

Body Material:

Plastic, mil-p-14, type mai-60

Body Style:

Panel mounted type

Terminal Material:

Copper, qq-c-502

Terminal Surface Treatment:

Silver plated, qq-s-365

Overall Length:

Between 5.844 inches and 5.906 inches

Mounting Hole Diameter:

Between 0.340 inches and 0.353 inches

Mounting Hole Quantity:

2

Overall Diameter:

Between 2.907 inches and 2.969 inches

Panel Thickness:

0.125 inches

Environmental Protection:

Any acceptable

Mounting Hole Style:

Bushing mounting w/2 holes

Contact Material:

Beryllium copper

Contact Surface Treatment:

Any acceptable

Interruption Indicator Method:

Incandescent lamp

Fuse Accommodation Quantity:

1

Accommodated Fuse Length:

3.000 inches

Accommodated Ferrule Diameter:

Between 0.781 inches and 0.843 inches

Length From Front Protrusion To Mounting Surface:

1.094 inches

Cap Diameter:

Between 1.594 inches and 1.656 inches

Center To Center Distance Between Outside Mounting Holes Along Length:

Between 2.370 inches and 2.380 inches

Bushing Hole Diameter:

Between 1.680 inches and 1.717 inches

Screw Thread Diameter:

0.250 inches

Screw Thready Qty Per Inch (tpi):

20.0

Current Carrying Rating In Amps:

60.0

Fuse Terminal Type Accommodated:

Ferrule

Voltage In Volts:

250.0

Terminal Type And Quantity:

2 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A014a0