NSN 5920-00-519-4274

Extractor Post Fuseholder - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5920-00-519-4274

Body Material:

Plastic, mil-p-14, type mai-60

Body Style:

Panel mounted type

Terminal Material:

Copper, qq-c-502

Terminal Surface Treatment:

Silver plated, qq-s-365

Overall Length:

Between 5.844 inches and 5.906 inches

Mounting Hole Diameter:

Between 0.340 inches and 0.353 inches

Mounting Hole Quantity:

Overall Diameter:

Between 2.907 inches and 2.969 inches

Panel Thickness:

0.125 inches

Environmental Protection:

Any acceptable

Mounting Hole Style:

Bushing mounting w/2 holes

Contact Material:

Beryllium copper

Contact Surface Treatment:

Any acceptable

Interruption Indicator Method:

Incandescent lamp

Fuse Accommodation Quantity:

Accommodated Fuse Length:

3.000 inches

Accommodated Ferrule Diameter:

Between 0.781 inches and 0.843 inches

Length From Front Protrusion To Mounting Surface:

1.094 inches

Cap Diameter:

Between 1.594 inches and 1.656 inches

Center To Center Distance Between Outside Mounting Holes Along Length:

Between 2.370 inches and 2.380 inches

Bushing Hole Diameter:

Between 1.680 inches and 1.717 inches

NSN 5920-00-519-4274Extractor Post Fuseholder - Page 2 of 2



| Screw Inread Diameter: |
|-----------------------------------|
| 0.250 inches |
| Screw Thready Qty Per Inch (tpi): |
| 20.0 |
| Current Carrying Rating In Amps: |
| 60.0 |
| Fuse Terminal Type Accommodated |
| Ferrule |
| Voltage In Volts: |
| 250.0 |
| Terminal Type And Quantity: |
| 2 threaded stud |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A014a0