NSN 5920-00-552-1310

Cartridge Fuse - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5920-00-552-1310 **Body Style:** Tangent terminal type **Terminal Material:** Brass **Terminal Surface Treatment:** Nickel **Overall Length:** Between 1.719 inches and 1.781 inches Center To Center Distance Between Mounting Facilities Parallel To Length: Between 0.969 inches and 1.031 inches **Overall Width:** Between 1.281 inches and 1.343 inches **Mounting Slot Width:** Between 0.259 inches and 0.260 inches **Overall Diameter:** Between 0.781 inches and 0.843 inches **Case Material:** Fiber and paper **Continuous Current Rating In Amps:** 40.000 **Terminal Thickness:** 0.047 inches **Maximum Voltage Rating In Volts:** 32.0 ac and 32.0 dc **Circuit Over-current Interruption Type:** Time delay **Interruption Indicator Method:** Opaque body **Features Provided:** Nonrenewable fusible element **Circuit Over-current Interruption Delay Time In Seconds:** 15.0 300 pct of current rating **Short-circuit/interrupt Current Rating In Amps:** 10000.0 **Test Data Document:** 81349-mil-f-15160 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Specification Data:**

N/a

Shelf Life:

Unit Of Measure:

81349-mil-f-15160/40 government specification

NSN 5920-00-552-1310

Cartridge Fuse - Page 2 of 2



Demilitarization:

No

Fiig:

A01700