Extractor Post Fuseholder - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5920-00-565-0032

| Body Material: | | |
|----------------------------|--------------------------|--|
| Plastic | | |
| | | |
| Body Style: | | |
| Bushing mounted type | | |
| Terminal Material: | | |
| Brass | | |
| Terminal Surface Treatme | π. | |
| Tin plated | | |
| Overall Length: | | |
| 2.453 inches | | |
| Bushing Diameter: | | |
| 0.625 inches | | |
| Mounting Hole Quantity: | | |
| 1 | | |
| Overall Diameter: | | |
| 0.812 inches | | |
| Environmental Protection: | | |
| Dripproof | | |
| Mounting Hole Style: | | |
| Bushing mounting | | |
| Contact Material: | | |
| Brass | | |
| Fuse Accommodation Qua | ntity: | |
| 1 | | |
| Accommodated Fuse Leng | th: | |
| 1.250 inches | | |
| Accommodated Ferrule Di | imeter: | |
| 0.250 inches | | |
| Length From Front Protrus | ion To Mounting Surface: | |
| 0.688 inches | | |
| Bushing Thread Length: | | |
| 0.469 inches | | |
| Cap Diameter: | | |
| 0.750 inches | | |
| Bushing Hole Diameter: | | |
| Between 0.625 inches and (| | |
| Flatted Side Bushing Hole | | |
| Between 0.585 inches and (| .595 inches | |
| Current Carrying Rating In | Amps: | |
| 18.0 | | |
| Fuse Terminal Type Accor | modated: | |
| Ferrule | | |

NSN 5920-00-565-0032

Extractor Post Fuseholder - Page 2 of 2

Voltage In Volts:

250.0

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A014a0

