

View Online at <https://aerobasegroup.com/nsn/5920-00-581-7957>

Body Material:

Plastic, diallyl phthalate, mil-m-14, type sdg

Body Style:

Bushing mounted type

Terminal Surface Treatment:

Solder dip and tin plated

Overall Length:

2.450 inches

Bushing Diameter:

0.625 inches

Mounting Hole Quantity:

1

Overall Diameter:

Between 0.790 inches and 0.830 inches

Environmental Protection:

Dripproof

Mounting Hole Style:

Bushing mounting

Contact Material:

Any acceptable

Contact Surface Treatment:

Silver plated, qq-s-365

Fuse Accommodation Quantity:

1

Accommodated Fuse Length:

1.250 inches

Accommodated Ferrule Diameter:

0.281 inches

Length From Front Protrusion To Mounting Surface:

Between 0.640 inches and 0.680 inches

Bushing Thread Length:

Between 0.480 inches and 0.520 inches

Cap Diameter:

Between 0.670 inches and 0.710 inches

Bushing Hole Diameter:

Between 0.625 inches and 0.635 inches

Flatted Side Bushing Hole Length:

Between 0.570 inches and 0.575 inches

Current Carrying Rating In Amps:

15.0

Fuse Terminal Type Accommodated:

Ferrule

Voltage In Volts:

250.0

Test Data Document:

81349-mil-f-19207/10 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A014a0