NSN 5920-00-581-7958

Extractor Post Fuseholder - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5920-00-581-7958

D ~ ~ .	Mate	swial.
Body	IVIATE	शाभाः

Plastic, diallyl phthalate, mil-m-14, type sdg and plastic, mil-p-14, type mai-60 and plastic, diallyl phthalate, mil-m-19833, type gdi-30f

Body Style:

Front panel mounted type

Terminal Material:

Copper

Terminal Surface Treatment:

Solder dip and tin plated

Overall Length:

2.531 inches

Overall Height:

Between 1.765 inches and 1.797 inches

Overall Width:

Between 1.109 inches and 1.141 inches

Mounting Hole Diameter:

Between 0.172 inches and 0.204 inches

Mounting Hole Quantity:

2

Environmental Protection:

Any acceptable

Mounting Hole Style:

Bushing mounting w/2 holes

Contact Material:

Any acceptable

Contact Surface Treatment:

Silver plated, qq-s-365

Fuse Accommodation Quantity:

•

Accommodated Fuse Length:

1.500 inches

Accommodated Ferrule Diameter:

0.406 inches

Length From Front Protrusion To Mounting Surface:

Between 0.718 inches and 0.750 inches

Cap Diameter:

Between 0.984 inches and 1.016 inches

Center To Center Distance Between Outside Mounting Holes Along Length:

Between 1.296 inches and 1.328 inches

Bushing Hole Diameter:

Between 0.875 inches and 0.907 inches

Current Carrying Rating In Amps:

30.0

NSN 5920-00-581-7958

Fiig: A014a0

Extractor Post Fuseholder - Page 2 of 2



Fuse Terminal Type Accommodated:
Ferrule
Voltage In Volts:
250.0
Test Data Document:
81349-mil-f-19207/14 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
2 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No