## NSN 5920-00-583-7989

Cartridge Fuse - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5920-00-583-7989 **Body Style:** Tangent terminal type **Terminal Material:** Brass **Overall Length:** Between 1.719 inches and 1.781 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 0.969 inches **Overall Height:** 1.031 inches **Overall Width:** Between 1.281 inches and 1.343 inches **Mounting Slot Width:** Between 0.259 inches and 0.260 inches **Overall Diameter:** Between 0.781 inches and 0.843 inches **Case Material:** Polyamide nylon and paper **Continuous Current Rating In Amps:** 60.000 **Terminal Thickness:** 0.047 inches **Maximum Voltage Rating In Volts:** 32.0 ac and 32.0 dc **Circuit Over-current Interruption Type:** Time delay **Interruption Indicator Method:** Opaque body **Features Provided:** Nonrenewable fusible element **Circuit Over-current Interruption Delay Time In Seconds:** 15.0 300 pct of current rating **Short-circuit/interrupt Current Rating In Amps:** 10000.0 **Test Data Document:** 81349-milf15160-40 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## **NSN 5920-00-583-7989**Cartridge Fuse - Page 2 of 2



Fiig:

A01700