

View Online at <https://aerobasegroup.com/nsn/5920-00-627-3717>

Body Material:

Plastic, mil-p-19833, type gdi-30f

Body Style:

Bushing mounted type

Overall Length:

3.310 inches

Bushing Diameter:

0.625 inches

Mounting Hole Quantity:

1

Overall Diameter:

0.810 inches

Environmental Protection:

Dripproof

Mounting Hole Style:

Bushing mounting

Lens Color:

Amber

Contact Material:

Beryllium copper

Contact Surface Treatment:

Any acceptable

Interruption Indicator Method:

Incandescent lamp

Fuse Accommodation Quantity:

1

Accommodated Fuse Length:

1.250 inches

Accommodated Ferrule Diameter:

0.250 inches

Resistor Rating:

330.0 ohms

Length From Front Protrusion To Mounting Surface:

1.190 inches

Bushing Thread Length:

0.440 inches

Cap Diameter:

0.530 inches

Bushing Hole Diameter:

Between 0.625 inches and 0.635 inches

Flatted Side Bushing Hole Length:

Between 0.570 inches and 0.575 inches

Current Carrying Rating In Amps:

20.0

Fuse Terminal Type Accommodated:

Ferrule

Voltage In Volts:

33.0

Test Data Document:

81349-mil-f-19207 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 tab, solder lug

Specification Data:

81349-mil-f-19207/9 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A014a0