NSN 5920-00-627-3781

Cartridge Fuse - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5920-00-627-3781

| Terminal Surface Treatment: Nickel Overall Length: 2.500 inches Overall Diameter: 0.812 inches Continuous Current Rating In Amps: 12.000 Maximum Voltage Rating In Volts: 600.0 ac Circuit Over-current Interruption Type: Normal instantaneous Interruption Indicator Method: Opaque body Features Provided: Nonrenewable fusible element Short-circuit/interrupt Current Rating In Amps: 20000.0 Special Features: Peak let-thru current Shelf Life: N/a Unit Of Measure: | Body Style: | |
|---|---|--|
| Nickel Nickel Overall Length: 2.500 inches Overall Diameter: 0.812 inches Continuous Current Rating In Amps: 12.000 Maximum Voltage Rating In Volts: 600.0 ac Circuit Over-current Interruption Type: Normal instantaneous Interruption Indicator Method: Opaque body Features Provided: Nonrenewable fusible element Short-circuit/interrupt Current Rating In Amps: 20000.0 Special Features: Peak let-thru current Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: | Tube type | |
| Overall Length: 2.500 inches Overall Diameter: 0.812 inches Continuous Current Rating In Amps: 12.000 Maximum Voltage Rating In Volts: 600.0 ac Circuit Over-current Interruption Type: Normal instantaneous Interruption Indicator Method: Opaque body Features Provided: Nonrenewable fusible element Short-circuit/interrupt Current Rating In Amps: 200000.0 Special Features: Peak let-thru current Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: | Terminal Surface Treatment: | |
| 2.500 inches Overall Diameter: 0.812 inches Continuous Current Rating In Amps: 12.000 Maximum Voltage Rating In Volts: 600.0 ac Circuit Over-current Interruption Type: Normal instantaneous Interruption Indicator Method: Opaque body Features Provided: Nonrenewable fusible element Short-circuit/interrupt Current Rating In Amps: 20000.0 Special Features: Peak let-thru current Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: | Nickel | |
| Overall Diameter: 0.812 inches Continuous Current Rating In Amps: 12.000 Maximum Voltage Rating In Volts: 600.0 ac Circuit Over-current Interruption Type: Normal instantaneous Interruption Indicator Method: Opaque body Features Provided: Nonrenewable fusible element Short-circuit/interrupt Current Rating In Amps: 20000.0 Special Features: Peak let-thru current Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: | Overall Length: | |
| 0.812 inches Continuous Current Rating In Amps: 12.000 Maximum Voltage Rating In Volts: 600.0 ac Circuit Over-current Interruption Type: Normal instantaneous Interruption Indicator Method: Opaque body Features Provided: Nonrenewable fusible element Short-circuit/interrupt Current Rating In Amps: 200000.0 Special Features: Peak let-thru current Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: | 2.500 inches | |
| Continuous Current Rating In Amps: 12.000 Maximum Voltage Rating In Volts: 600.0 ac Circuit Over-current Interruption Type: Normal instantaneous Interruption Indicator Method: Opaque body Features Provided: Nonrenewable fusible element Short-circuit/interrupt Current Rating In Amps: 200000.0 Special Features: Peak let-thru current Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: | Overall Diameter: | |
| 12.000 Maximum Voltage Rating In Volts: 600.0 ac Circuit Over-current Interruption Type: Normal instantaneous Interruption Indicator Method: Opaque body Features Provided: Nonrenewable fusible element Short-circuit/interrupt Current Rating In Amps: 200000.0 Special Features: Peak let-thru current Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | 0.812 inches | |
| Maximum Voltage Rating In Volts: 600.0 ac Circuit Over-current Interruption Type: Normal instantaneous Interruption Indicator Method: Opaque body Features Provided: Nonrenewable fusible element Short-circuit/interrupt Current Rating In Amps: 200000.0 Special Features: Peak let-thru current Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: | Continuous Current Rating In Amps: | |
| 600.0 ac Circuit Over-current Interruption Type: Normal instantaneous Interruption Indicator Method: Opaque body Features Provided: Nonrenewable fusible element Short-circuit/interrupt Current Rating In Amps: 200000.0 Special Features: Peak let-thru current Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: | 12.000 | |
| Circuit Over-current Interruption Type: Normal instantaneous Interruption Indicator Method: Opaque body Features Provided: Nonrenewable fusible element Short-circuit/interrupt Current Rating In Amps: 200000.0 Special Features: Peak let-thru current Shelf Life: N/a Unit Of Measure: Demilitarization: No | Maximum Voltage Rating In Volts: | |
| Normal instantaneous Interruption Indicator Method: Opaque body Features Provided: Nonrenewable fusible element Short-circuit/interrupt Current Rating In Amps: 200000.0 Special Features: Peak let-thru current Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | 600.0 ac | |
| Interruption Indicator Method: Opaque body Features Provided: Nonrenewable fusible element Short-circuit/interrupt Current Rating In Amps: 200000.0 Special Features: Peak let-thru current Shelf Life: N/a Unit Of Measure: Demilitarization: No | Circuit Over-current Interruption Type: | |
| Opaque body Features Provided: Nonrenewable fusible element Short-circuit/interrupt Current Rating In Amps: 200000.0 Special Features: Peak let-thru current Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | Normal instantaneous | |
| Features Provided: Nonrenewable fusible element Short-circuit/interrupt Current Rating In Amps: 200000.0 Special Features: Peak let-thru current Shelf Life: N/a Unit Of Measure: Demilitarization: No | Interruption Indicator Method: | |
| Nonrenewable fusible element Short-circuit/interrupt Current Rating In Amps: 200000.0 Special Features: Peak let-thru current Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | Opaque body | |
| Short-circuit/interrupt Current Rating In Amps: 200000.0 Special Features: Peak let-thru current Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | Features Provided: | |
| 200000.0 Special Features: Peak let-thru current Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | Nonrenewable fusible element | |
| Special Features: Peak let-thru current Shelf Life: N/a Unit Of Measure: Demilitarization: No Filg: | Short-circuit/interrupt Current Rating In Amps: | |
| Peak let-thru current Shelf Life: N/a Unit Of Measure: Demilitarization: No Filg: | 200000.0 | |
| Shelf Life: N/a Unit Of Measure: Demilitarization: No Filg: | Special Features: | |
| N/a Unit Of Measure: Demilitarization: No Fiig: | Peak let-thru current | |
| Unit Of Measure: Demilitarization: No Filg: | Shelf Life: | |
| Demilitarization: No Fiig: | N/a | |
| Demilitarization: No Filg: | Unit Of Measure: | |
| No Fiig: | | |
| Fiig: | Demilitarization: | |
| • | No | |
| 101700 | Fiig: | |
| A01700 | A01700 | |
| | | |