## NSN 5920-00-647-3467

Extractor Post Fuseholder - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5920-00-647-3467 **Body Material:** Plastic, diallyl phthalate, mil-m-14, type sdg **Body Style:** Bushing mounted type **Terminal Surface Treatment:** Solder dip **Overall Length:** 2.812 inches **Bushing Diameter:** 0.625 inches **Overall Width:** 1.125 inches **Body Diameter:** 0.812 inches **Environmental Protection:** Dripproof **Mounting Hole Style: Bushing mounting Contact Material: Brass Contact Surface Treatment:** Silver plated **Interruption Indicator Method:** Neon lamp **Fuse Accommodation Quantity:** 1 **Accommodated Fuse Length:** 1.250 inches **Accommodated Ferrule Diameter:** 0.250 inches **Resistor Rating:** 470.0 kilohms **Indicating Lamp Voltage Range In Volts:** +250.0/+400.0 **Length From Front Protrusion To Mounting Surface:** 1.188 inches **Bushing Thread Length:** 0.438 inches Cap Diameter: 0.500 inches

**Bushing Hole Diameter:** 

Between 0.625 inches and 0.635 inches

## **NSN 5920-00-647-3467**Extractor Post Fuseholder - Page 2 of 2



Flatted Side Bushing Hole Length:
Between 0.585 inches and 0.595 inches
Current Carrying Rating In Amps:
20.0
Fuse Terminal Type Accommodated:
Ferrule
Voltage In Volts:
400.0
Precious Material And Location:
Contact surface silver
Precious Material:
Silver
Terminal Type And Quantity:
2 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Filg:

A014a0