NSN 5920-00-655-1149

Cartridge Fuse - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5920-00-655-1149 **Body Style:** Tube type **Terminal Material:** Brass or copper or copper alloy **Terminal Surface Treatment:** Silver plated **Overall Length:** Between 1.469 inches and 1.531 inches **Overall Diameter:** Between 0.402 inches and 0.410 inches Case Material: Glass **Continuous Current Rating In Amps:** 1.000 **Fragility Factor:** Moderately delicate **Maximum Voltage Rating In Volts:** 125.0 ac and 125.0 dc **Circuit Over-current Interruption Type:** Time delay **Interruption Indicator Method:** Visible element **Features Provided:** Nonrenewable fusible element **Circuit Over-current Interruption Delay Time In Seconds:** 12.0 200 pct of current rating **Short-circuit/interrupt Current Rating In Amps:** 10000.0 **Precious Material And Location:** Terminal surfaces silver **Precious Material:** Silver **Test Data Document:** 81349-mil-f-15160 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Specification Data:** 81349-mil-f-15160/7 government specification Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5920-00-655-1149Cartridge Fuse - Page 2 of 2



Fiig:

A01700