## NSN 5920-00-660-6018

Extractor Post Fuseholder - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5920-00-660-6018 **Body Style:** Panel mounted type **Overall Length:** 3.875 inches **Overall Height:** 1.188 inches **Overall Width:** 1.188 inches **Mounting Hole Diameter:** 0.156 inches **Mounting Hole Quantity: Environmental Protection:** Any acceptable **Mounting Hole Style:** 2 bushing mounting w/2 holes **Contact Material:** Beryllium copper **Contact Surface Treatment:** Any acceptable **Interruption Indicator Method:** Neon lamp **Fuse Accommodation Quantity: Accommodated Fuse Length:** 1.250 inches **Accommodated Ferrule Diameter:** 0.250 inches **Resistor Rating:** 12.0 kilohms and 12.0 kilohms **Indicating Lamp Voltage Range In Volts:** +23.0/+33.0 **Length From Front Protrusion To Mounting Surface:** 0.812 inches **Center To Center Distance Between Outside Mounting Holes Along Width:** 0.938 inches **Bushing Hole Diameter:** 0.974 inches **Center To Center Distance Between Bushing Holes:** 0.938 inches

Center To Center Distance Between Keyway And Bushing Hole:

0.469 inches

## **NSN 5920-00-660-6018**Extractor Post Fuseholder - Page 2 of 2



Screw Inread Diameter:
0.164 inches
Screw Thready Qty Per Inch (tpi):
32.0
Current Carrying Rating In Amps:
30.0
Fuse Terminal Type Accommodated
Ferrule
Voltage In Volts:
250.0
Terminal Type And Quantity:
4 threaded stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A014a0