

View Online at <https://aerobasegroup.com/nsn/5920-00-660-6018>

Body Style:

Panel mounted type

Overall Length:

3.875 inches

Overall Height:

1.188 inches

Overall Width:

1.188 inches

Mounting Hole Diameter:

0.156 inches

Mounting Hole Quantity:

2

Environmental Protection:

Any acceptable

Mounting Hole Style:

2 bushing mounting w/2 holes

Contact Material:

Beryllium copper

Contact Surface Treatment:

Any acceptable

Interruption Indicator Method:

Neon lamp

Fuse Accommodation Quantity:

2

Accommodated Fuse Length:

1.250 inches

Accommodated Ferrule Diameter:

0.250 inches

Resistor Rating:

12.0 kilohms and 12.0 kilohms

Indicating Lamp Voltage Range In Volts:

+23.0/+33.0

Length From Front Protrusion To Mounting Surface:

0.812 inches

Center To Center Distance Between Outside Mounting Holes Along Width:

0.938 inches

Bushing Hole Diameter:

0.974 inches

Center To Center Distance Between Bushing Holes:

0.938 inches

Center To Center Distance Between Keyway And Bushing Hole:

0.469 inches

Screw Thread Diameter:

0.164 inches

Screw Thready Qty Per Inch (tpi):

32.0

Current Carrying Rating In Amps:

30.0

Fuse Terminal Type Accommodated:

Ferrule

Voltage In Volts:

250.0

Terminal Type And Quantity:

4 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A014a0