

View Online at <https://aerobasegroup.com/nsn/5920-00-683-4915>

Body Material:

Plastic, diallyl phthalate, mil-m-14, type sdg or plastic, diallyl phthalate, mil-m-19833, type gdi-30f

Body Style:

Front panel mounted type

Terminal Material:

Copper alloy

Terminal Surface Treatment:

Tin plated

Overall Length:

Between 2.590 inches and 2.630 inches

Bushing Diameter:

Between 0.980 inches and 1.020 inches

Overall Height:

Between 1.760 inches and 1.800 inches

Overall Width:

Between 1.100 inches and 1.140 inches

Mounting Hole Diameter:

Between 0.178 inches and 0.181 inches

Mounting Hole Quantity:

2

Environmental Protection:

Watertight

Mounting Hole Style:

Bushing mounting w/2 holes

Lens Color:

Clear

Fragility Factor:

Moderately rugged

Contact Material:

Copper alloy

Contact Surface Treatment:

Nickel plated

Interruption Indicator Method:

Visual indicating

Fuse Accommodation Quantity:

1

Accommodated Fuse Length:

1.500 inches

Accommodated Ferrule Diameter:

0.406 inches

Length From Front Protrusion To Mounting Surface:

Between 0.810 inches and 0.850 inches

Cap Diameter:

Between 0.980 inches and 1.020 inches

Center To Center Distance Between Outside Mounting Holes Along Length:

Between 1.307 inches and 1.317 inches

Bushing Hole Diameter:

Between 0.980 inches and 1.020 inches

Current Carrying Rating In Amps:

20.0

Fuse Terminal Type Accommodated:

Ferrule

Voltage In Volts:

250.0

Test Data Document:

81349-mil-f-19207 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 tab, solder lug

Specification Data:

81349-mil-f-19207/12 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A014a0