NSN 5920-00-685-9892

Block Fuseholder - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5920-00-685-9892

Body Material:

Plastic, melamine, mil-m-14, type mme and plastic, silicone, mil-m-14, type msi-30

Body Style:

Side barrier type

Terminal Surface Treatment:

Cadmium, qq-p-416

Overall Length:

Between 3.094 inches and 3.156 inches

Overall Height:

0.938 inches

Overall Width:

1.188 inches

Mounting Hole Diameter:

Between 0.204 inches and 0.210 inches

Mounting Hole Quantity:

2

Base Thickness:

Between 0.268 inches and 0.312 inches

Mounting Hole Style:

Diagonal to the left

Contact Material:

Copper-beryllium, qq-c-530 or copper-beryllium, qq-c-533

Contact Surface Treatment:

Silver plated, qq-s-365

Fuse Accommodation Quantity:

2

Accommodated Fuse Length:

0.328 inches

Center To Center Distance Between Outside Mounting Holes Along Length:

Between 0.484 inches and 0.516 inches

Center To Center Distance Between Outside Mounting Holes Along Width:

Between 0.484 inches and 0.516 inches

Current Carrying Rating In Amps:

30.0

Internal Circuit Configuration And Pole Quantity:

2 pole, mainline, fused

Fuse Terminal Type Accommodated:

Knife blade

Test Data Document:

81349-mil-f-5373c specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

4 screw

NSN 5920-00-685-9892

Block Fuseholder - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A014a0