

View Online at <https://aerobasegroup.com/nsn/5920-00-687-1896>

Body Material:

Plastic, diallyl phthalate, mil-m-14, type sdg

Body Style:

Front panel mounted type

Terminal Surface Treatment:

Solder dip and tin plated

Overall Length:

2.484 inches

Overall Height:

Between 1.760 inches and 1.800 inches

Overall Width:

Between 1.180 inches and 1.220 inches

Mounting Hole Diameter:

Between 0.170 inches and 0.210 inches

Mounting Hole Quantity:

2

Environmental Protection:

Watertight

Mounting Hole Style:

Bushing mounting w/2 holes

Contact Material:

Any acceptable

Contact Surface Treatment:

Silver plated, qq-s-365

Fuse Accommodation Quantity:

1

Accommodated Fuse Length:

1.500 inches

Accommodated Ferrule Diameter:

0.406 inches

Length From Front Protrusion To Mounting Surface:

Between 0.830 inches and 0.870 inches

Cap Diameter:

Between 1.010 inches and 1.050 inches

Center To Center Distance Between Outside Mounting Holes Along Length:

Between 1.307 inches and 1.317 inches

Bushing Hole Diameter:

Between 0.870 inches and 0.910 inches

Current Carrying Rating In Amps:

30.0

Fuse Terminal Type Accommodated:

Ferrule

Voltage In Volts:

250.0

Test Data Document:

81349-mil-f-19207/13 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A014a0