

View Online at <https://aerobasegroup.com/nsn/5920-00-687-1896>

**Body Material:**

Plastic, diallyl phthalate, mil-m-14, type sdg

**Body Style:**

Front panel mounted type

**Terminal Surface Treatment:**

Solder dip and tin plated

**Overall Length:**

2.484 inches

**Overall Height:**

Between 1.760 inches and 1.800 inches

**Overall Width:**

Between 1.180 inches and 1.220 inches

**Mounting Hole Diameter:**

Between 0.170 inches and 0.210 inches

**Mounting Hole Quantity:**

2

**Environmental Protection:**

Watertight

**Mounting Hole Style:**

Bushing mounting w/2 holes

**Contact Material:**

Any acceptable

**Contact Surface Treatment:**

Silver plated, qq-s-365

**Fuse Accommodation Quantity:**

1

**Accommodated Fuse Length:**

1.500 inches

**Accommodated Ferrule Diameter:**

0.406 inches

**Length From Front Protrusion To Mounting Surface:**

Between 0.830 inches and 0.870 inches

**Cap Diameter:**

Between 1.010 inches and 1.050 inches

**Center To Center Distance Between Outside Mounting Holes Along Length:**

Between 1.307 inches and 1.317 inches

**Bushing Hole Diameter:**

Between 0.870 inches and 0.910 inches

**Current Carrying Rating In Amps:**

30.0

**Fuse Terminal Type Accommodated:**

Ferrule

**Voltage In Volts:**

250.0

**Test Data Document:**

81349-mil-f-19207/13 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

2 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A014a0