

View Online at <https://aerobasegroup.com/nsn/5920-00-714-8847>

**Body Material:**

Plastic, diallyl phthalate, mil-m-14, type mdg

**Body Style:**

Panel mounted type

**Terminal Material:**

Brass

**Terminal Surface Treatment:**

Any acceptable

**Overall Length:**

3.062 inches

**Bushing Diameter:**

0.875 inches

**Overall Height:**

Between 1.812 inches and 1.817 inches

**Overall Width:**

Between 1.302 inches and 1.313 inches

**Mounting Hole Diameter:**

0.156 inches

**Mounting Hole Quantity:**

2

**Environmental Protection:**

Dripproof and fungus proof

**Mounting Hole Style:**

2 bushing mounting w/2 holes

**Contact Material:**

Copper-beryllium, qq-c-530

**Contact Surface Treatment:**

Silver plated, qq-s-365

**Fuse Accommodation Quantity:**

1

**Accommodated Fuse Length:**

1.250 inches

**Accommodated Ferrule Diameter:**

0.250 inches

**Length From Front Protrusion To Mounting Surface:**

Any acceptable

**Center To Center Distance Between Outside Mounting Holes Along Width:**

0.984 inches

**Bushing Hole Diameter:**

0.875 inches

**Center To Center Distance Between Bushing Holes:**

0.800 inches

**Center To Center Distance Between Keyway And Bushing Hole:**

Any acceptable

**Screw Thread Diameter:**

0.164 inches

**Screw Thready Qty Per Inch (tpi):**

32.0

**Current Carrying Rating In Amps:**

30.0

**Fuse Terminal Type Accommodated:**

Ferrule

**Voltage In Volts:**

250.0

**Precious Material And Location:**

Contacts silver

**Precious Material:**

Silver

**Terminal Type And Quantity:**

4 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A014a0