NSN 5920-00-728-3487

Plastic, phenolic, mil-m-14, type cfg

Body Material:

Body Style:

Bushing mounted type

Terminal Material:

Extractor Post Fuseholder - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5920-00-728-3487

Terminal Surface Treatment:
Solder dip
Overall Length:
2.219 inches
Bushing Diameter:
0.500 inches
Mounting Hole Quantity:
1
Overall Diameter:
Between 0.703 inches and 0.735 inches
Environmental Protection:
Any acceptable
Mounting Hole Style:
Bushing mounting
Contact Material:
Beryllium copper
Contact Surface Treatment:
Nickel plated
Fuse Accommodation Quantity:
1
Accommodated Fuse Length:
1.250 inches
Accommodated Ferrule Diameter:
Accommodated Ferrule Diameter: 0.250 inches
0.250 inches
0.250 inches Length From Front Protrusion To Mounting Surface:
0.250 inches Length From Front Protrusion To Mounting Surface: 0.500 inches
0.250 inches Length From Front Protrusion To Mounting Surface: 0.500 inches Bushing Thread Length:
0.250 inches Length From Front Protrusion To Mounting Surface: 0.500 inches Bushing Thread Length: Between 0.469 inches and 0.531 inches
0.250 inches Length From Front Protrusion To Mounting Surface: 0.500 inches Bushing Thread Length: Between 0.469 inches and 0.531 inches Cap Diameter:
0.250 inches Length From Front Protrusion To Mounting Surface: 0.500 inches Bushing Thread Length: Between 0.469 inches and 0.531 inches Cap Diameter: 0.719 inches
0.250 inches Length From Front Protrusion To Mounting Surface: 0.500 inches Bushing Thread Length: Between 0.469 inches and 0.531 inches Cap Diameter: 0.719 inches Bushing Hole Diameter:
0.250 inches Length From Front Protrusion To Mounting Surface: 0.500 inches Bushing Thread Length: Between 0.469 inches and 0.531 inches Cap Diameter: 0.719 inches Bushing Hole Diameter: Between 0.500 inches and 0.510 inches
0.250 inches Length From Front Protrusion To Mounting Surface: 0.500 inches Bushing Thread Length: Between 0.469 inches and 0.531 inches Cap Diameter: 0.719 inches Bushing Hole Diameter: Between 0.500 inches and 0.510 inches Flatted Side Bushing Hole Length:
0.250 inches Length From Front Protrusion To Mounting Surface: 0.500 inches Bushing Thread Length: Between 0.469 inches and 0.531 inches Cap Diameter: 0.719 inches Bushing Hole Diameter: Between 0.500 inches and 0.510 inches Flatted Side Bushing Hole Length: Between 0.468 inches and 0.478 inches

NSN 5920-00-728-3487Extractor Post Fuseholder - Page 2 of 2



Fuse Terminal Type Accommodated:
Ferrule
Voltage In Volts:
250.0
Terminal Type And Quantity:
2 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A014a0