

View Online at <https://aerobasegroup.com/nsn/5920-00-728-6521>

**Body Material:**

Plastic, diallyl phthalate, mil-m-14, type sdg

**Body Style:**

Panel mounted type

**Overall Length:**

Between 5.445 inches and 5.495 inches

**Mounting Hole Diameter:**

Between 0.265 inches and 0.270 inches

**Mounting Hole Quantity:**

2

**Overall Diameter:**

Between 2.870 inches and 2.880 inches

**Panel Thickness:**

0.187 inches

**Environmental Protection:**

Dripproof

**Mounting Hole Style:**

Bushing mounting w/2 holes

**Contact Material:**

Any acceptable

**Contact Surface Treatment:**

Silver plated, qq-s-365

**Interruption Indicator Method:**

Neon lamp

**Fuse Accommodation Quantity:**

1

**Accommodated Fuse Length:**

3.000 inches

**Accommodated Ferrule Diameter:**

0.813 inches

**Resistor Rating:**

160.0 kilohms and 160.0 kilohms

**Indicating Lamp Voltage Range In Volts:**

+90.0/+500.0 and +90.0/+500.0

**Length From Front Protrusion To Mounting Surface:**

Between 1.200 inches and 1.240 inches

**Cap Diameter:**

Between 1.980 inches and 2.020 inches

**Center To Center Distance Between Outside Mounting Holes Along Length:**

Between 2.370 inches and 2.380 inches

**Bushing Hole Diameter:**

1.755 inches

**Screw Thread Diameter:**

0.250 inches

**Screw Thready Qty Per Inch (tpi):**

20.0

**Current Carrying Rating In Amps:**

60.0

**Fuse Terminal Type Accommodated:**

Ferrule

**Voltage In Volts:**

500.0

**Test Data Document:**

81349-mil-f-19207 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

2 threaded stud

**Specification Data:**

81349-mil-f-19207/5 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A014a0