NSN 5920-00-752-3030

Extractor Post Fuseholder - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5920-00-752-3030
Body Material:
Plastic, diallyl phthalate, mil-m-14, type sdg
Body Style:
Panel mounted type
Terminal Material:
Brass
Overall Length:
Between 3.750 inches and 4.000 inches
Overall Height:
Between 1.812 inches and 1.817 inches
Overall Width:
Between 1.180 inches and 1.185 inches
Mounting Hole Diameter:
Between 0.151 inches and 0.161 inches
Mounting Hole Quantity:
2
Environmental Protection:
Dripproof
Mounting Hole Style:
2 bushing mounting w/2 holes
Lens Color:
Amber
Contact Material:
Beryllium copper
Contact Surface Treatment:
Silver plated, qq-s-365
Interruption Indicator Method:
Incandescent lamp
Fuse Accommodation Quantity:
2
Accommodated Fuse Length:
1.250 inches
Accommodated Ferrule Diameter:
0.250 inches
Length From Front Protrusion To Mounting Surface:
Between 0.798 inches and 0.828 inches
Center To Center Distance Between Outside Mounting Holes Along Width:
Between 0.933 inches and 0.943 inches
Bushing Hole Diameter:
Between 0.869 inches and 0.879 inches
Center To Center Distance Between Bushing Holes:

Between 0.795 inches and 0.805 inches

NSN 5920-00-752-3030Extractor Post Fuseholder - Page 2 of 2



Center To Center Distance Between Keyway And Bushing Hole:
Between 0.464 inches and 0.474 inches
Screw Thread Diameter:
0.164 inches
Screw Thready Qty Per Inch (tpi):
32.0
Current Carrying Rating In Amps:
30.0
Fuse Terminal Type Accommodated:
Ferrule
Voltage In Volts:
22.0
Precious Material And Location:
Contact surfaces silver
Precious Material:
Silver
Test Data Document:
31349-mil-f-19207 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Ferminal Type And Quantity:
4 threaded stud
Specification Data:
31349-mil-f-19207/18 government specification
Shelf Life:
N/a
Jnit Of Measure:
-
Demilitarization:
No
Filg:
A014a0