# NSN 5920-00-755-3656

Cartridge Fuse - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5920-00-755-3656

# Body Style:

Tube type

**Terminal Material:** 

Brass or copper or copper alloy

# **Terminal Surface Treatment:**

Nickel

#### **Overall Length:**

Between 1.219 inches and 1.281 inches

#### **Overall Diameter:**

Between 0.246 inches and 0.254 inches

#### **Case Material:**

Ceramic or plastic

**Continuous Current Rating In Amps:** 

30.000

Maximum Voltage Rating In Volts:

125.0 ac and 125.0 dc

# **Circuit Over-current Interruption Type:**

Time delay

# Interruption Indicator Method:

Opaque body

# Features Provided:

Nonrenewable fusible element

# Circuit Over-current Interruption Delay Time In Seconds:

12.0 200 pct of current rating

# Short-circuit/interrupt Current Rating In Amps:

10000.0

# Test Data Document:

81349-mil-f-15160 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Specification Data:**

81349-mil-f-15160/3 government specification

# Shelf Life:

N/a

#### Unit Of Measure:

--

# Demilitarization:

No

Fiig:

A01700

# Mil-std (military Standard):

Mil-prf-15160 spec.