

View Online at <https://aerobasegroup.com/nsn/5920-00-760-6284>

**Body Style:**

Panel mounted type

**Overall Length:**

4.000 inches

**Mounting Hole Diameter:**

0.205 inches

**Mounting Hole Quantity:**

2

**Overall Diameter:**

2.375 inches

**Panel Thickness:**

0.187 inches

**Environmental Protection:**

Dripproof

**Mounting Hole Style:**

Bushing mounting w/2 holes

**Contact Material:**

Copper

**Contact Surface Treatment:**

Any acceptable

**Interruption Indicator Method:**

Neon lamp

**Fuse Accommodation Quantity:**

1

**Accommodated Fuse Length:**

2.000 inches

**Accommodated Ferrule Diameter:**

0.563 inches

**Resistor Rating:**

160.0 kilohms

**Indicating Lamp Voltage Range In Volts:**

+90.0/+500.0

**Length From Front Protrusion To Mounting Surface:**

1.000 inches

**Cap Diameter:**

1.625 inches

**Center To Center Distance Between Outside Mounting Holes Along Length:**

1.880 inches

**Bushing Hole Diameter:**

1.375 inches

**Screw Thread Diameter:**

0.190 inches

**Screw Thready Qty Per Inch (tpi):**

24.0

**Current Carrying Rating In Amps:**

30.0

**Criticality Code Justification:**

Feat

**Fuse Terminal Type Accommodated:**

Ferrule

**Voltage In Volts:**

500.0

**Special Features:**

Item must comply w/rqmts of desc production standard no. L00682

**Terminal Type And Quantity:**

2 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A014a0