

View Online at <https://aerobasegroup.com/nsn/5920-00-760-6284>

Body Style:

Panel mounted type

Overall Length:

4.000 inches

Mounting Hole Diameter:

0.205 inches

Mounting Hole Quantity:

2

Overall Diameter:

2.375 inches

Panel Thickness:

0.187 inches

Environmental Protection:

Dripproof

Mounting Hole Style:

Bushing mounting w/2 holes

Contact Material:

Copper

Contact Surface Treatment:

Any acceptable

Interruption Indicator Method:

Neon lamp

Fuse Accommodation Quantity:

1

Accommodated Fuse Length:

2.000 inches

Accommodated Ferrule Diameter:

0.563 inches

Resistor Rating:

160.0 kilohms

Indicating Lamp Voltage Range In Volts:

+90.0/+500.0

Length From Front Protrusion To Mounting Surface:

1.000 inches

Cap Diameter:

1.625 inches

Center To Center Distance Between Outside Mounting Holes Along Length:

1.880 inches

Bushing Hole Diameter:

1.375 inches

Screw Thread Diameter:

0.190 inches

Screw Thready Qty Per Inch (tpi):

24.0

Current Carrying Rating In Amps:

30.0

Criticality Code Justification:

Feat

Fuse Terminal Type Accommodated:

Ferrule

Voltage In Volts:

500.0

Special Features:

Item must comply w/rqmts of desc production standard no. L00682

Terminal Type And Quantity:

2 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A014a0