

View Online at <https://aerobasegroup.com/nsn/5920-00-770-2015>

Body Material:

Glass

Body Style:

Bushing mounted type

Terminal Material:

Brass

Terminal Surface Treatment:

Silver plated

Overall Length:

2.625 inches

Bushing Diameter:

0.625 inches

Mounting Hole Diameter:

0.125 inches and 0.875 inches

Mounting Hole Quantity:

1 and 1

Overall Diameter:

1.000 inches

Panel Thickness:

0.125 inches

Environmental Protection:

Shock proof and vibration proof

Mounting Hole Style:

Bushing mounting w/one hole

Lens Color:

Clear

Contact Material:

Beryllium copper

Contact Surface Treatment:

Silver plated

Interruption Indicator Method:

Neon lamp

Fuse Accommodation Quantity:

1

Accommodated Fuse Length:

1.250 inches

Accommodated Ferrule Diameter:

0.250 inches

Length From Front Protrusion To Mounting Surface:

1.531 inches

Bushing Thread Length:

0.843 inches

Cap Diameter:

1.000 inches

Bushing Hole Diameter:

0.875 inches

Center To Center Distance Between Bushing Hole And Mounting Hole:

0.625 inches

Screw Thread Diameter:

0.312 inches

Screw Thready Qty Per Inch (tpi):

24.0

Current Carrying Rating In Amps:

30.0

Fuse Terminal Type Accommodated:

Ferrule

Voltage In Volts:

250.0

Precious Material And Location:

Contacts silver and terminals silver

Precious Material:

Silver

Terminal Type And Quantity:

2 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A014a0