

View Online at <https://aerobasegroup.com/nsn/5920-00-770-2015>

**Body Material:**

Glass

**Body Style:**

Bushing mounted type

**Terminal Material:**

Brass

**Terminal Surface Treatment:**

Silver plated

**Overall Length:**

2.625 inches

**Bushing Diameter:**

0.625 inches

**Mounting Hole Diameter:**

0.125 inches and 0.875 inches

**Mounting Hole Quantity:**

1 and 1

**Overall Diameter:**

1.000 inches

**Panel Thickness:**

0.125 inches

**Environmental Protection:**

Shock proof and vibration proof

**Mounting Hole Style:**

Bushing mounting w/one hole

**Lens Color:**

Clear

**Contact Material:**

Beryllium copper

**Contact Surface Treatment:**

Silver plated

**Interruption Indicator Method:**

Neon lamp

**Fuse Accommodation Quantity:**

1

**Accommodated Fuse Length:**

1.250 inches

**Accommodated Ferrule Diameter:**

0.250 inches

**Length From Front Protrusion To Mounting Surface:**

1.531 inches

**Bushing Thread Length:**

0.843 inches

**Cap Diameter:**

1.000 inches

**Bushing Hole Diameter:**

0.875 inches

**Center To Center Distance Between Bushing Hole And Mounting Hole:**

0.625 inches

**Screw Thread Diameter:**

0.312 inches

**Screw Thread Qty Per Inch (tpi):**

24.0

**Current Carrying Rating In Amps:**

30.0

**Fuse Terminal Type Accommodated:**

Ferrule

**Voltage In Volts:**

250.0

**Precious Material And Location:**

Contacts silver and terminals silver

**Precious Material:**

Silver

**Terminal Type And Quantity:**

2 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A014a0