

View Online at <https://aerobasegroup.com/nsn/5920-00-781-7191>

Body Material:

Plastic, diallyl phthalate, mil-m-14, type sdg

Body Style:

Panel mounted type

Terminal Material:

Brass

Overall Length:

4.000 inches

Mounting Hole Diameter:

Between 0.205 inches and 0.210 inches

Mounting Hole Quantity:

2

Overall Diameter:

Between 2.370 inches and 2.380 inches

Panel Thickness:

0.187 inches

Environmental Protection:

Dripproof

Mounting Hole Style:

Bushing mounting w/2 holes

Lens Color:

Clear

Contact Material:

Bronze, spring

Contact Surface Treatment:

Silver plated, qq-s-365

Interruption Indicator Method:

Neon lamp

Fuse Accommodation Quantity:

1

Accommodated Fuse Length:

2.000 inches

Accommodated Ferrule Diameter:

0.563 inches

Resistor Rating:

160.0 kilohms

Indicating Lamp Voltage Range In Volts:

+90.0/+500.0

Length From Front Protrusion To Mounting Surface:

Between 0.980 inches and 1.020 inches

Cap Diameter:

1.630 inches

Center To Center Distance Between Outside Mounting Holes Along Length:

Between 1.870 inches and 1.880 inches

Bushing Hole Diameter:

Between 1.370 inches and 1.380 inches

Screw Thread Diameter:

0.190 inches

Screw Thread Qty Per Inch (tpi):

24.0

Current Carrying Rating In Amps:

30.0

Fuse Terminal Type Accommodated:

Ferrule

Voltage In Volts:

500.0

Precious Material And Location:

Contact surfaces silver

Precious Material:

Silver

Test Data Document:

81349-mil-f-19207 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 threaded stud

Specification Data:

81349-mil-f-19207/4 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A014a0