

View Online at <https://aerobasegroup.com/nsn/5920-00-797-9957>

Overall Length:

3.281 inches

Bushing Diameter:

0.625 inches

Overall Diameter:

0.812 inches

Environmental Protection:

Vibration proof

Mounting Hole Style:

Bushing mounting

Lens Color:

Amber

Contact Material:

Beryllium copper

Contact Surface Treatment:

Silver plated

Interruption Indicator Method:

Neon lamp

Fuse Accommodation Quantity:

1

Accommodated Fuse Length:

1.250 inches

Accommodated Ferrule Diameter:

0.250 inches

Indicating Lamp Voltage Range In Volts:

+24.0/+32.0

Length From Front Protrusion To Mounting Surface:

1.188 inches

Bushing Thread Length:

0.438 inches

Cap Diameter:

0.812 inches

Bushing Hole Diameter:

Between 0.625 inches and 0.635 inches

Flatted Side Bushing Hole Length:

Between 0.585 inches and 0.595 inches

Current Carrying Rating In Amps:

20.0

Fuse Terminal Type Accommodated:

Ferrule

Voltage In Volts:

32.0

Terminal Type And Quantity:

2 tab, solder lug

Reference Number Differentiating Characteristics:

As differentiated by navord od 42046

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A014a0