

View Online at <https://aerobasegroup.com/nsn/5920-00-798-8861>

Body Material:

Plastic, diallyl phthalate, mil-m-14, type sdg and plastic, diallyl phthalate, mil-m-19833, type gdi-30f

Body Style:

Bushing mounted type

Terminal Surface Treatment:

Solder dip and tin plated

Overall Length:

2.380 inches

Bushing Diameter:

0.625 inches

Mounting Hole Quantity:

1

Overall Diameter:

Between 0.920 inches and 0.960 inches

Environmental Protection:

Dripproof

Mounting Hole Style:

Bushing mounting

Contact Material:

Any acceptable

Contact Surface Treatment:

Silver plated, qq-s-365

Interruption Indicator Method:

Incandescent lamp

Fuse Accommodation Quantity:

1

Accommodated Fuse Length:

1.250 inches

Accommodated Ferrule Diameter:

0.250 inches

Resistor Rating:

680.0 ohms

Indicating Lamp Voltage Range In Volts:

+34.0/+45.0

Length From Front Protrusion To Mounting Surface:

Between 0.820 inches and 0.860 inches

Bushing Thread Length:

Between 0.420 inches and 0.460 inches

Bushing Hole Diameter:

Between 0.625 inches and 0.635 inches

Flatted Side Bushing Hole Length:

Between 0.570 inches and 0.575 inches

Current Carrying Rating In Amps:

20.0

Fuse Terminal Type Accommodated:

Ferrule

Voltage In Volts:

60.0

Test Data Document:

81349-mil-f-19207/9 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A014a0