

View Online at <https://aerobasegroup.com/nsn/5920-00-802-0666>

**Body Material:**

Plastic, phenolic, moulded

**Body Style:**

Panel mounted type

**Overall Length:**

3.938 inches

**Keyway Width:**

Any acceptable

**Mounting Hole Diameter:**

Between 0.166 inches and 0.176 inches

**Mounting Hole Quantity:**

2

**Overall Diameter:**

1.312 inches

**Panel Thickness:**

Any acceptable

**Environmental Protection:**

Shock proof and vibration proof

**Mounting Hole Style:**

Bushing mounting w/2 holes and keyway

**Contact Material:**

Bronze

**Contact Surface Treatment:**

Silver plated

**Interruption Indicator Method:**

Neon lamp

**Fuse Accommodation Quantity:**

1

**Accommodated Fuse Length:**

1.500 inches

**Accommodated Ferrule Diameter:**

0.406 inches

**Length From Front Protrusion To Mounting Surface:**

1.001 inches

**Cap Diameter:**

0.683 inches

**Center To Center Distance Between Outside Mounting Holes Along Length:**

1.124 inches

**Center To Center Distance Between Outside Mounting Holes Along Width:**

1.125 inches

**Bushing Hole Diameter:**

1.000 inches

**Center To Center Distance Between Keyway And Bushing Hole:**

0.562 inches

**Screw Thread Diameter:**

0.164 inches

**Screw Thready Qty Per Inch (tpi):**

36.0

**Current Carrying Rating In Amps:**

20.0

**Fuse Terminal Type Accommodated:**

Ferrule

**Voltage In Volts:**

125.0

**Terminal Type And Quantity:**

2 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A014a0