

View Online at <https://aerobasegroup.com/nsn/5920-00-802-0666>

Body Material:

Plastic, phenolic, moulded

Body Style:

Panel mounted type

Overall Length:

3.938 inches

Keyway Width:

Any acceptable

Mounting Hole Diameter:

Between 0.166 inches and 0.176 inches

Mounting Hole Quantity:

2

Overall Diameter:

1.312 inches

Panel Thickness:

Any acceptable

Environmental Protection:

Shock proof and vibration proof

Mounting Hole Style:

Bushing mounting w/2 holes and keyway

Contact Material:

Bronze

Contact Surface Treatment:

Silver plated

Interruption Indicator Method:

Neon lamp

Fuse Accommodation Quantity:

1

Accommodated Fuse Length:

1.500 inches

Accommodated Ferrule Diameter:

0.406 inches

Length From Front Protrusion To Mounting Surface:

1.001 inches

Cap Diameter:

0.683 inches

Center To Center Distance Between Outside Mounting Holes Along Length:

1.124 inches

Center To Center Distance Between Outside Mounting Holes Along Width:

1.125 inches

Bushing Hole Diameter:

1.000 inches

Center To Center Distance Between Keyway And Bushing Hole:

0.562 inches

Screw Thread Diameter:

0.164 inches

Screw Thready Qty Per Inch (tpi):

36.0

Current Carrying Rating In Amps:

20.0

Fuse Terminal Type Accommodated:

Ferrule

Voltage In Volts:

125.0

Terminal Type And Quantity:

2 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A014a0