

View Online at <https://aerobasegroup.com/nsn/5920-00-813-9121>

**Body Style:**

Bushing mounted type

**Overall Length:**

2.312 inches

**Bushing Diameter:**

0.500 inches

**Overall Diameter:**

0.688 inches

**Environmental Protection:**

Fungus proof and salt spray proof

**Mounting Hole Style:**

Bushing mounting

**Contact Material:**

Beryllium copper

**Contact Surface Treatment:**

Silver plated

**Interruption Indicator Method:**

Test hole

**Fuse Accommodation Quantity:**

1

**Accommodated Fuse Length:**

1.250 inches

**Accommodated Ferrule Diameter:**

0.250 inches

**Length From Front Protrusion To Mounting Surface:**

0.688 inches

**Bushing Thread Length:**

0.438 inches

**Cap Diameter:**

0.688 inches

**Bushing Hole Diameter:**

Between 0.500 inches and 0.510 inches

**Flatted Side Bushing Hole Length:**

Between 0.468 inches and 0.478 inches

**Current Carrying Rating In Amps:**

15.0

**Fuse Terminal Type Accommodated:**

Ferrule

**Voltage In Volts:**

250.0

**Terminal Type And Quantity:**

2 tab, solder lug

**Reference Number Differentiating Characteristics:**

As differentiated by navord od41152

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A014a0