

View Online at <https://aerobasegroup.com/nsn/5920-00-813-9121>

Body Style:

Bushing mounted type

Overall Length:

2.312 inches

Bushing Diameter:

0.500 inches

Overall Diameter:

0.688 inches

Environmental Protection:

Fungus proof and salt spray proof

Mounting Hole Style:

Bushing mounting

Contact Material:

Beryllium copper

Contact Surface Treatment:

Silver plated

Interruption Indicator Method:

Test hole

Fuse Accommodation Quantity:

1

Accommodated Fuse Length:

1.250 inches

Accommodated Ferrule Diameter:

0.250 inches

Length From Front Protrusion To Mounting Surface:

0.688 inches

Bushing Thread Length:

0.438 inches

Cap Diameter:

0.688 inches

Bushing Hole Diameter:

Between 0.500 inches and 0.510 inches

Flatted Side Bushing Hole Length:

Between 0.468 inches and 0.478 inches

Current Carrying Rating In Amps:

15.0

Fuse Terminal Type Accommodated:

Ferrule

Voltage In Volts:

250.0

Terminal Type And Quantity:

2 tab, solder lug

Reference Number Differentiating Characteristics:

As differentiated by navord od41152

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A014a0