

View Online at <https://aerobasegroup.com/nsn/5920-00-819-6939>

**Body Material:**

Plastic

**Body Style:**

Bushing mounted type

**Terminal Material:**

Any acceptable

**Terminal Surface Treatment:**

Electrotinned

**Overall Length:**

Between 2.125 inches and 2.157 inches

**Bushing Diameter:**

0.500 inches

**Mounting Hole Quantity:**

1

**Overall Diameter:**

Between 0.672 inches and 0.704 inches

**Environmental Protection:**

Fungus proof

**Mounting Hole Style:**

Bushing mounting

**Contact Material:**

Copper

**Contact Surface Treatment:**

Tin plated

**Interruption Indicator Method:**

Test hole

**Fuse Accommodation Quantity:**

1

**Accommodated Fuse Length:**

1.000 inches

**Accommodated Ferrule Diameter:**

0.250 inches

**Length From Front Protrusion To Mounting Surface:**

0.594 inches

**Bushing Thread Length:**

Between 0.484 inches and 0.516 inches

**Cap Diameter:**

Between 0.672 inches and 0.704 inches

**Bushing Hole Diameter:**

Between 0.500 inches and 0.510 inches

**Flatted Side Bushing Hole Length:**

Between 0.468 inches and 0.478 inches

**Current Carrying Rating In Amps:**

5.0

**Fuse Terminal Type Accommodated:**

Ferrule

**Voltage In Volts:**

125.0

**Terminal Type And Quantity:**

2 ferrule

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A014a0