

View Online at <https://aerobasegroup.com/nsn/5920-00-819-6939>

Body Material:

Plastic

Body Style:

Bushing mounted type

Terminal Material:

Any acceptable

Terminal Surface Treatment:

Electrotinned

Overall Length:

Between 2.125 inches and 2.157 inches

Bushing Diameter:

0.500 inches

Mounting Hole Quantity:

1

Overall Diameter:

Between 0.672 inches and 0.704 inches

Environmental Protection:

Fungus proof

Mounting Hole Style:

Bushing mounting

Contact Material:

Copper

Contact Surface Treatment:

Tin plated

Interruption Indicator Method:

Test hole

Fuse Accommodation Quantity:

1

Accommodated Fuse Length:

1.000 inches

Accommodated Ferrule Diameter:

0.250 inches

Length From Front Protrusion To Mounting Surface:

0.594 inches

Bushing Thread Length:

Between 0.484 inches and 0.516 inches

Cap Diameter:

Between 0.672 inches and 0.704 inches

Bushing Hole Diameter:

Between 0.500 inches and 0.510 inches

Flatted Side Bushing Hole Length:

Between 0.468 inches and 0.478 inches

Current Carrying Rating In Amps:

5.0

Fuse Terminal Type Accommodated:

Ferrule

Voltage In Volts:

125.0

Terminal Type And Quantity:

2 ferrule

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A014a0