

View Online at <https://aerobasegroup.com/nsn/5920-00-823-0906>

Body Style:

Panel mounted type

Overall Length:

Between 3.750 inches and 4.000 inches

Overall Height:

Between 1.812 inches and 1.817 inches

Overall Width:

Between 1.180 inches and 1.185 inches

Mounting Hole Diameter:

0.156 inches

Mounting Hole Quantity:

2

Environmental Protection:

Dripproof

Mounting Hole Style:

2 bushing mounting w/2 holes

Contact Material:

Beryllium copper

Contact Surface Treatment:

Silver plated, qq-s-365

Interruption Indicator Method:

Incandescent lamp

Fuse Accommodation Quantity:

2

Accommodated Fuse Length:

1.250 inches

Accommodated Ferrule Diameter:

0.250 inches

Resistor Rating:

2.0 kilohms and 2.0 kilohms

Indicating Lamp Voltage Range In Volts:

+81.0/+90.0 and +81.0/+90.0

Length From Front Protrusion To Mounting Surface:

Between 0.798 inches and 0.828 inches

Center To Center Distance Between Outside Mounting Holes Along Width:

0.938 inches

Bushing Hole Diameter:

0.874 inches

Center To Center Distance Between Bushing Holes:

0.800 inches

Center To Center Distance Between Keyway And Bushing Hole:

0.434 inches

Screw Thread Diameter:

0.164 inches

Screw Thready Qty Per Inch (tpi):

32.0

Current Carrying Rating In Amps:

30.0

Fuse Terminal Type Accommodated:

Ferrule

Voltage In Volts:

90.0

Test Data Document:

81349-mil-f-19207/18d specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

4 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A014a0