

View Online at <https://aerobasegroup.com/nsn/5920-00-823-0907>

**Body Style:**

Panel mounted type

**Overall Length:**

Between 3.750 inches and 4.000 inches

**Overall Height:**

1.813 inches

**Overall Width:**

1.188 inches

**Mounting Hole Quantity:**

2

**Environmental Protection:**

Dripproof

**Mounting Hole Style:**

2 bushing mounting w/2 holes

**Contact Material:**

Beryllium copper

**Contact Surface Treatment:**

Silver plated, qq-s-365

**Interruption Indicator Method:**

Neon lamp

**Fuse Accommodation Quantity:**

2

**Accommodated Fuse Length:**

1.250 inches

**Accommodated Ferrule Diameter:**

0.250 inches

**Resistor Rating:**

120.0 kilohms

**Indicating Lamp Voltage Range In Volts:**

+90.0/+250.0

**Length From Front Protrusion To Mounting Surface:**

0.813 inches

**Center To Center Distance Between Outside Mounting Holes Along Width:**

0.938 inches

**Screw Thread Diameter:**

0.164 inches

**Current Carrying Rating In Amps:**

30.0

**Fuse Terminal Type Accommodated:**

Ferrule

**Voltage In Volts:**

250.0

**Test Data Document:**

81349-mil-f-19207/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

4 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A014a0