

View Online at <https://aerobasegroup.com/nsn/5920-00-824-1515>

Body Material:

Plastic, diallyl phthalate, mil-m-14, type sdg

Body Style:

Rear panel mounted type

Overall Length:

Between 4.000 inches and 4.250 inches

Overall Height:

Between 1.370 inches and 1.380 inches

Overall Width:

Between 1.370 inches and 1.380 inches

Mounting Hole Diameter:

Between 0.151 inches and 0.161 inches

Mounting Hole Quantity:

4

Environmental Protection:

Any acceptable

Mounting Hole Style:

Bushing mounting w/4 holes

Contact Material:

Any acceptable

Contact Surface Treatment:

Silver plated, qq-s-365

Interruption Indicator Method:

Neon lamp

Fuse Accommodation Quantity:

1

Accommodated Fuse Length:

1.500 inches

Accommodated Ferrule Diameter:

0.406 inches

Resistor Rating:

330.0 kilohms

Indicating Lamp Voltage Range In Volts:

+90.0/+500.0

Length From Front Protrusion To Mounting Surface:

Between 0.798 inches and 0.828 inches

Center To Center Distance Between Outside Mounting Holes Along Length:

Between 1.057 inches and 1.067 inches

Center To Center Distance Between Outside Mounting Holes Along Width:

Between 1.057 inches and 1.067 inches

Bushing Hole Diameter:

Between 1.135 inches and 1.145 inches

Center To Center Distance Between Bushing Hole And Mounting Hole:

Between 0.526 inches and 0.536 inches

Screw Thread Diameter:

0.164 inches

Screw Thready Qty Per Inch (tpi):

32.0

Current Carrying Rating In Amps:

30.0

Fuse Terminal Type Accommodated:

Ferrule

Voltage In Volts:

500.0

Test Data Document:

81349-mil-f-19207/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A014a0