## NSN 5920-00-824-1515

Extractor Post Fuseholder - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5920-00-824-1515

**Body Material:** 

Plastic, diallyl phthalate, mil-m-14, type sdg

**Body Style:** 

Rear panel mounted type

**Overall Length:** 

Between 4.000 inches and 4.250 inches

**Overall Height:** 

Between 1.370 inches and 1.380 inches

**Overall Width:** 

Between 1.370 inches and 1.380 inches

**Mounting Hole Diameter:** 

Between 0.151 inches and 0.161 inches

**Mounting Hole Quantity:** 

1

**Environmental Protection:** 

Any acceptable

**Mounting Hole Style:** 

Bushing mounting w/4 holes

**Contact Material:** 

Any acceptable

**Contact Surface Treatment:** 

Silver plated, qq-s-365

**Interruption Indicator Method:** 

Neon lamp

**Fuse Accommodation Quantity:** 

1

**Accommodated Fuse Length:** 

1.500 inches

**Accommodated Ferrule Diameter:** 

0.406 inches

**Resistor Rating:** 

330.0 kilohms

**Indicating Lamp Voltage Range In Volts:** 

+90.0/+500.0

**Length From Front Protrusion To Mounting Surface:** 

Between 0.798 inches and 0.828 inches

Center To Center Distance Between Outside Mounting Holes Along Length:

Between 1.057 inches and 1.067 inches

**Center To Center Distance Between Outside Mounting Holes Along Width:** 

Between 1.057 inches and 1.067 inches

**Bushing Hole Diameter:** 

Between 1.135 inches and 1.145 inches

## NSN 5920-00-824-1515

Extractor Post Fuseholder - Page 2 of 2



Center To Center Distance Between Bushing Hole And Mounting Hole:
Between 0.526 inches and 0.536 inches
Screw Thread Diameter:
0.164 inches
Screw Thready Qty Per Inch (tpi):
32.0
Current Carrying Rating In Amps:
30.0
Fuse Terminal Type Accommodated:
Ferrule
Voltage In Volts:
500.0
Test Data Document:
81349-mil-f-19207/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
2 threaded stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A014a0