

NSN 5920-00-829-1463 Extractor Post Fuseholder - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5920-00-829-1463 **Body Material:** Plastic, phenolic, moulded **Body Style:** Bushing mounted type

**Terminal Material:** 

**Brass** 

**Terminal Surface Treatment:** 

Solder dip

**Overall Length:** 

2.750 inches

**Bushing Diameter:** 

0.875 inches

**Mounting Hole Quantity:** 

**Overall Diameter:** 

Between 1.188 inches and 1.218 inches

**Environmental Protection:** 

Watertight and body sealed

**Mounting Hole Style:** 

**Bushing mounting** 

**Lens Color:** 

Clear

**Contact Material:** 

Beryllium copper

**Contact Surface Treatment:** 

Copper and tin plated and zinc plated

**Interruption Indicator Method:** 

Incandescent lamp

**Fuse Accommodation Quantity:** 

**Accommodated Fuse Length:** 

1.500 inches **Accommodated Ferrule Diameter:** 

0.406 inches

**Resistor Rating:** 

330.0 ohms

**Indicating Lamp Voltage Range In Volts:** 

+24.0/+32.0

**Length From Front Protrusion To Mounting Surface:** 

0.828 inches

**Bushing Thread Length:** 

Between 0.516 inches and 0.546 inches

## NSN 5920-00-829-1463

Extractor Post Fuseholder - Page 2 of 2



Cap Diameter:
Between 1.094 inches and 1.124 inches
Bushing Hole Diameter:
Between 0.860 inches and 0.865 inches
Flatted Side Bushing Hole Length:
Between 0.810 inches and 0.815 inches
Current Carrying Rating In Amps:
30.0
Fuse Terminal Type Accommodated:
Ferrule
Voltage In Volts:
250.0
Terminal Type And Quantity:
2 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A014a0