

View Online at <https://aerobasegroup.com/nsn/5920-00-837-6833>

Body Material:

Plastic, diallyl phthalate, mil-m-14, type sdg and plastic, diallyl phthalate, mil-m-19833, type gdi-30f

Body Style:

Panel mounted type

Terminal Surface Treatment:

Silver plated, qq-s-365

Overall Length:

3.875 inches

Overall Height:

1.812 inches

Overall Width:

1.188 inches

Mounting Hole Diameter:

0.156 inches

Mounting Hole Quantity:

2

Environmental Protection:

Dripproof

Mounting Hole Style:

2 bushing mounting w/2 holes

Contact Material:

Beryllium copper

Contact Surface Treatment:

Silver plated, qq-s-365

Interruption Indicator Method:

Incandescent lamp

Fuse Accommodation Quantity:

2

Accommodated Fuse Length:

1.250 inches

Accommodated Ferrule Diameter:

0.250 inches

Resistor Rating:

120.0 kilohms

Indicating Lamp Voltage Range In Volts:

+24.0/+36.0

Length From Front Protrusion To Mounting Surface:

0.812 inches

Center To Center Distance Between Outside Mounting Holes Along Width:

0.938 inches

Bushing Hole Diameter:

0.874 inches

Center To Center Distance Between Bushing Holes:

0.800 inches

Center To Center Distance Between Keyway And Bushing Hole:

0.469 inches

Screw Thread Diameter:

0.250 inches

Screw Thread Qty Per Inch (tpi):

32.0

Current Carrying Rating In Amps:

36.0

Fuse Terminal Type Accommodated:

Ferrule

Voltage In Volts:

250.0

Precious Material And Location:

Contact and terminal surfaces silver

Precious Material:

Silver

Terminal Type And Quantity:

4 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A014a0