NSN 5920-00-841-7283

Extractor Post Fuseholder - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5920-00-841-7283 **Body Material:** Plastic, phenolic, moulded **Body Style:** Panel mounted type **Terminal Material: Brass Overall Length:** 2.720 inches **Overall Height:** 2.880 inches **Overall Width:** 1.190 inches **Mounting Hole Diameter:** 0.152 inches and 0.781 inches **Mounting Hole Quantity:** 3 and 4 **Environmental Protection:** Watertight and body sealed **Mounting Hole Style:** 3 bushing mounting w/4 holes **Contact Material:** Copper **Fuse Accommodation Quantity: Accommodated Fuse Length:** 1.500 inches **Accommodated Ferrule Diameter:** 0.406 inches **Length From Front Protrusion To Mounting Surface:**

0.560 inches

Cap Diameter:

0.880 inches

Center To Center Distance Between Outside Mounting Holes Along Length:

1.002 inches

Center To Center Distance Between Outside Mounting Holes Along Width:

0.502 inches

Bushing Hole Diameter:

Between 0.771 inches and 0.786 inches

Center To Center Distance Between Bushing Holes:

Between 0.994 inches and 1.009 inches

Err Default:

Err default and err default

NSN 5920-00-841-7283Extractor Post Fuseholder - Page 2 of 2



Screw Thread Diameter:
0.190 inches
Screw Thready Qty Per Inch (tpi):
32.0
Current Carrying Rating In Amps:
30.0
Fuse Terminal Type Accommodated:
Ferrule
Voltage In Volts:
500.0
Test Data Document:
81349-mil-f-19207 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
3 threaded stud and 3 screw
Specification Data:
81349-mil-f-19207/31 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A014a0