

View Online at <https://aerobasegroup.com/nsn/5920-00-841-9929>

**Body Material:**

Plastic, diallyl phthalate, mil-m-14, type mdg and plastic, diallyl phthalate, mil-m-14, type sdg and plastic, melamine, mil-m-14, type mme and plastic, silicone, mil-m-14, type msg

**Body Style:**

Clip connected type

**Terminal Material:**

Copper-beryllium, qq-c-530 or copper-beryllium, qq-c-533

**Terminal Surface Treatment:**

Solder dip and tin plated

**Overall Length:**

Between 3.730 inches and 3.770 inches

**Overall Height:**

Between 1.140 inches and 1.180 inches

**Overall Width:**

Between 0.995 inches and 1.005 inches

**Mounting Hole Diameter:**

0.190 inches

**Mounting Hole Quantity:**

1

**Base Thickness:**

Between 0.360 inches and 0.400 inches

**Mounting Hole Style:**

One hole mounting

**Contact Material:**

Copper-beryllium, qq-c-530 or copper-beryllium, qq-c-533

**Contact Surface Treatment:**

Silver plated, qq-s-365

**Fuse Accommodation Quantity:**

1

**Accommodated Fuse Length:**

3.031 inches

**Accommodated Ferrule Diameter:**

Between 0.402 inches and 0.410 inches

**Current Carrying Rating In Amps:**

2.0

**Internal Circuit Configuration And Pole Quantity:**

1 pole, mainline, fused

**Fuse Terminal Type Accommodated:**

Ferrule

**Voltage In Volts:**

1000.0

**Test Data Document:**

81349-mil-f-21346 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical" "average" "" etc.)

**Terminal Type And Quantity:**

2 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A014a0