NSN 5920-00-841-9929

Block Fuseholder - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5920-00-841-9929

Body Material:

Plastic, diallyl phthalate, mil-m-14, type mdg and plastic, diallyl phthalate, mil-m-14, type sdg and plastic, melamine, mil-m-14, type mme and plastic, silicone, mil-m-14, type msg

Body Style:

Clip connected type

Terminal Material:

Copper-beryllium, qq-c-530 or copper-beryllium, qq-c-533

Terminal Surface Treatment:

Solder dip and tin plated

Overall Length:

Between 3.730 inches and 3.770 inches

Overall Height:

Between 1.140 inches and 1.180 inches

Overall Width:

Between 0.995 inches and 1.005 inches

Mounting Hole Diameter:

0.190 inches

Mounting Hole Quantity:

1

Base Thickness:

Between 0.360 inches and 0.400 inches

Mounting Hole Style:

One hole mounting

Contact Material:

Copper-beryllium, qq-c-530 or copper-beryllium, qq-c-533

Contact Surface Treatment:

Silver plated, qq-s-365

Fuse Accommodation Quantity:

1

Accommodated Fuse Length:

3.031 inches

Accommodated Ferrule Diameter:

Between 0.402 inches and 0.410 inches

Current Carrying Rating In Amps:

2.0

Internal Circuit Configuration And Pole Quantity:

1 pole, mainline, fused

Fuse Terminal Type Accommodated:

Ferrule

Voltage In Volts:

1000.0

Test Data Document:

81349-mil-f-21346 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

NSN 5920-00-841-9929

Block Fuseholder - Page 2 of 2



Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A014a0