NSN 5920-00-842-3028

Cartridge Fuse - Page 1 of 2

Fiig: A01700



View Online at https://aerobasegroup.com/nsn/5920-00-842-3028

View Online at https://aerobasegroup.com/nsn/5920-00-842-3028
Body Style:
Tube type
Terminal Material:
Brass
Terminal Surface Treatment:
Silver plated
Overall Length:
Between 1.469 inches and 1.531 inches
Overall Diameter:
Between 0.402 inches and 0.410 inches
Case Material:
Fiber
Continuous Current Rating In Amps:
0.300
Maximum Voltage Rating In Volts:
250.0 ac and 250.0 dc
Circuit Over-current Interruption Type:
Time delay
Interruption Indicator Method:
Opaque body
Features Provided:
Nonrenewable fusible element
Circuit Over-current Interruption Delay Time In Seconds:
12.0 200 pct of current rating
Short-circuit/interrupt Current Rating In Amps:
10000.0
Precious Material And Location:
Terminals silver
Precious Material:
Silver
Test Data Document:
81349-mil-f-15160 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-f-15160/9b government specification
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No

NSN 5920-00-842-3028

Cartridge Fuse - Page 2 of 2



Mil-std (military Standard):

Mil-prf-15160 spec.