

View Online at <https://aerobasegroup.com/nsn/5920-00-842-3494>

**Body Material:**

Plastic, diallyl phthalate, mil-m-14, type mdg and plastic, diallyl phthalate, mil-m-14, type sdg and plastic, melamine, mil-m-14, type mme and plastic, silicone, mil-m-14, type msg

**Body Style:**

Clip connected type

**Terminal Material:**

Copper-beryllium, qq-c-530 or copper-beryllium, qq-c-533

**Terminal Surface Treatment:**

Solder dip and tin plated

**Overall Length:**

Between 1.360 inches and 1.400 inches

**Overall Height:**

Between 0.680 inches and 0.720 inches

**Overall Width:**

Between 4.860 inches and 4.900 inches

**Mounting Hole Diameter:**

0.138 inches

**Mounting Hole Quantity:**

1

**Base Thickness:**

Between 0.230 inches and 0.270 inches

**Mounting Hole Style:**

One hole mounting

**Contact Material:**

Copper-beryllium, qq-c-530 or copper-beryllium, qq-c-533

**Contact Surface Treatment:**

Copper and tin plated and zinc plated

**Fuse Accommodation Quantity:**

8

**Accommodated Fuse Length:**

Between 0.969 inches and 1.031 inches

**Accommodated Ferrule Diameter:**

Between 0.246 inches and 0.254 inches

**Current Carrying Rating In Amps:**

2.0

**Internal Circuit Configuration And Pole Quantity:**

8 pole, mainline, fused

**Fuse Terminal Type Accommodated:**

Ferrule

**Voltage In Volts:**

250.0

**Test Data Document:**

81349-mil-f-21346 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical" "average" "" etc.)

**Terminal Type And Quantity:**

16 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A014a0