NSN 5920-00-843-2286

Cartridge Fuse - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5920-00-843-2286 |
|--|
| Body Style: |
| Axial terminal type |
| Terminal Material: |
| Brass |
| Terminal Surface Treatment: |
| Nickel |
| Overall Length: |
| 3.625 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| Between 2.969 inches and 3.031 inches |
| Mounting Slot Width: |
| Between 0.235 inches and 0.297 inches |
| Body Length: |
| Between 2.094 inches and 2.156 inches |
| Overall Diameter: |
| Between 0.781 inches and 0.843 inches |
| Case Material: |
| Fiber |
| Continuous Current Rating In Amps: |
| 40.000 |
| Terminal Width: |
| Between 0.657 inches and 0.719 inches |
| Maximum Voltage Rating In Volts: |
| 125.0 ac and 125.0 dc |
| Circuit Over-current Interruption Type: |
| Normal instantaneous |
| Interruption Indicator Method: |
| Opaque body |
| Features Provided: |
| Nonrenewable fusible element |
| Short-circuit/interrupt Current Rating In Amps: |
| 10000.0 |
| Test Data Document: |
| 81349-mil-f-15160 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Specification Data: |
| 81349-mil-f-15160/38 government specification |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

NSN 5920-00-843-2286Cartridge Fuse - Page 2 of 2



Fiig:

A01700