

View Online at <https://aerobasegroup.com/nsn/5920-00-844-6510>

Body Style:

Bushing mounted type

Overall Length:

2.620 inches

Bushing Diameter:

0.875 inches

Mounting Hole Quantity:

1

Overall Diameter:

1.120 inches

Panel Thickness:

0.125 inches

Environmental Protection:

Watertight and salt spray proof

Mounting Hole Style:

Bushing mounting

Lens Color:

Clear

Contact Material:

Beryllium copper

Contact Surface Treatment:

Silver plated

Interruption Indicator Method:

Neon lamp

Fuse Accommodation Quantity:

1

Accommodated Fuse Length:

1.250 inches

Accommodated Ferrule Diameter:

0.250 inches

Resistor Rating:

120.0 kilohms

Length From Front Protrusion To Mounting Surface:

1.120 inches

Bushing Thread Length:

0.438 inches

Cap Diameter:

1.000 inches

Bushing Hole Diameter:

Between 0.877 inches and 0.882 inches

Flatted Side Bushing Hole Length:

Between 0.816 inches and 0.821 inches

Screw Thread Diameter:

0.138 inches

Screw Thready Qty Per Inch (tpi):

32.0

Current Carrying Rating In Amps:

30.0

Fuse Terminal Type Accommodated:

Ferrule

Voltage In Volts:

55.0

Terminal Type And Quantity:

1 threaded stud and 1 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A014a0