

View Online at <https://aerobasegroup.com/nsn/5920-00-844-6511>

**Body Style:**

Bushing mounted type

**Overall Length:**

2.620 inches

**Bushing Diameter:**

0.875 inches

**Mounting Hole Quantity:**

1

**Overall Diameter:**

1.120 inches

**Panel Thickness:**

0.125 inches

**Environmental Protection:**

Watertight and salt spray proof

**Mounting Hole Style:**

Bushing mounting

**Lens Color:**

Clear

**Contact Material:**

Beryllium copper

**Contact Surface Treatment:**

Silver plated

**Interruption Indicator Method:**

Neon lamp

**Fuse Accommodation Quantity:**

1

**Accommodated Fuse Length:**

1.250 inches

**Accommodated Ferrule Diameter:**

0.250 inches

**Resistor Rating:**

120.0 kilohms

**Length From Front Protrusion To Mounting Surface:**

1.120 inches

**Bushing Thread Length:**

0.438 inches

**Cap Diameter:**

1.000 inches

**Bushing Hole Diameter:**

Between 0.877 inches and 0.882 inches

**Flatted Side Bushing Hole Length:**

Between 0.816 inches and 0.821 inches

**Screw Thread Diameter:**

0.138 inches

**Screw Thready Qty Per Inch (tpi):**

32.0

**Current Carrying Rating In Amps:**

30.0

**Fuse Terminal Type Accommodated:**

Ferrule

**Voltage In Volts:**

15.0

**Terminal Type And Quantity:**

1 threaded stud and 1 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A014a0