

View Online at <https://aerobasegroup.com/nsn/5920-00-849-5762>

**Body Material:**

Plastic

**Body Style:**

Bushing mounted type

**Terminal Surface Treatment:**

Solder dip

**Overall Length:**

2.281 inches

**Bushing Diameter:**

0.500 inches

**Mounting Hole Quantity:**

1

**Overall Diameter:**

0.688 inches

**Environmental Protection:**

Dripproof

**Mounting Hole Style:**

Bushing mounting

**Contact Material:**

Brass

**Contact Surface Treatment:**

Solder dip

**Interruption Indicator Method:**

Test hole

**Fuse Accommodation Quantity:**

1

**Accommodated Fuse Length:**

1.250 inches

**Accommodated Ferrule Diameter:**

0.250 inches

**Length From Front Protrusion To Mounting Surface:**

0.625 inches

**Bushing Thread Length:**

0.469 inches

**Cap Diameter:**

0.688 inches

**Bushing Hole Diameter:**

Between 0.500 inches and 0.510 inches

**Flatted Side Bushing Hole Length:**

Between 0.468 inches and 0.478 inches

**Current Carrying Rating In Amps:**

15.0

**Fuse Terminal Type Accommodated:**

Ferrule

**Voltage In Volts:**

250.0

**Test Data Document:**

08903-bac31c1 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

2 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A014a0